





HY-YJ203S



HY-YJ203D



适用范围 The scope of application

适用于各类船舶通道和应急出口等场所作出口及通道指示。
Fit for exit and alleyway indication in ships for the passage and emergency exit.

产品特点 Products characteristic




自动应急照明时间不少于180min。
The time of automatic emergency illumination is not less than 180min.

规格specification

型号Type	电压/频率Voltage/Frequency	功率Power	防护等级Protection Class	重量 Weight	安装方式 Mounting mode
HY-YJ203S	220V/50Hz	2W	IP22	3.0 kg	吊挂式pendant
HY-YJ203D				3.0 kg	



HY-YJ204



适用范围 The scope of application

适用于各类船舶通道和应急出口等场所作出口及通道指示。
Fit for exit and alleyway indication in ships for the passage and emergency exit.

产品特点 Products characteristic

自动应急照明时间不少于180min。壳体采用优质铝材，标识牌采用有机玻璃雕刻，透光性能极好。
The time of automatic emergency illumination is not less than 180min.
The body adopt the good quality aluminium, the signboard is engraved by synthetic glass, has excellent transparent property

规格specification:

型号Type	电压/频率Voltage/Frequency	功率Power	光源illuminant	防护等级Protection Class	重量 Weight	安装方式 Mounting mode
HY-YJ204	~220V/50Hz	2W	LED	IP22	0.7 kg	吊挂式 pendant 壁式 wall-type 吸顶式 ceiling-type